

VirGin LVT Specifications

Type & Composition		PVC Laminated Floor Covering
Application		Commercial, Residential
Surface Treatment		PU & Anti-bacterial, Per design
Profile		Beveled / Non-beveled, Per design
Tile Size (mm)	EN 427	180 x 1220
Total Thickness (mm)	EN 4.3	4
Wear Layer Thickness (mm)	EN 429	0.3 0.5 0.7
Fire Rating	EN 13501-1	B _{fl} - S1
	Mekel Bumer Test	Pass
Heat Stability	KSM 3802	0.3mm / 0.01 (80 °C + 2°C, 6hr / hr)
Slip Resistance	BS 7976-2	PVC Laminated Floor Covering RZ Surface Roughness : Moderate
Residual Indentation	EN 433	≤ 0.10 mm
Color Fastness	ISO 105-B02	≥ 6
Dimensional Stability	EN 434	≤ 0.25 %
Flexibility	EN 435	No Crack was found
Electrical Behavior	EN 1081	Pass

VirGin Tiles - Glueless Luxury vinyl plank & tiles

- Individual Glass Fiber Layer
- Extra Flexibility Over Any Surfaces
- Organic-Inorganic Hybrid Antimicrobial Technology
- 0.3/0.5mm Micro-Ceramic Wear Layer
- Waterproof / Easy Clean
- Fire / Slip / Oil / Stain Resistant
- No Glue / No Underlay
- 4 Side Micro Bevel
- 2 Coats PU



4 Side Micro Bevel



Quick and Easy Click Installation



Dimensions

Thickness	Size(W×L)
4 mm	1220 X 180 X 4mm
5mm	620 X 310 X 4mm
7 mm	

► can be adjustable

